

# AGRIMAX SPARGO

<b>TIRE SIZE</b>	<b>VF 480/80 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	176 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94075317	<b>RC (IN)</b>	219.4
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	72.2	<b>RIM ALT</b>	DW 15 L
<b>SLR (IN)</b>	33.0	<b>ECE</b>	E11-106R-009072

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	20	23	26	29	32	35	38	41	44	47	49	52
<b>45</b>	8110	8980	9850	10280	10860	11150	11440	12020	12600	13030	13610	14050	14480
<b>FROM 40 TO 25</b>	8770	9720	10640	11120	11740	12060	12370	12990	13630	14090	14720	15190	15660
<b>20</b>	8940	9910	10860	11350	11990	12310	12630	13250	13900	14390	15020	15500	15980
<b>12</b>	9120	10100	11070	11570	12220	12550	12870	13520	14170	14660	15300	15800	16290
<b>5*</b>	9650	10690	11710	12230	12920	13270	13610	14290	14980	15500	16190	16700	17220
<b>UPTO 20 CYCLIC</b>	9960	11030	12090	12610	13330	13690	14050	14750	15470	16000	16700	17240	17770
<b>UPTO 10 CYCLIC</b>	11890	13170	14420	15060	15920	16340	16770	17610	18470	19110	19940	20580	21220
<b>UPTO 5 CYCLIC</b>	13150	14570	15970	16680	17630	18090	18560	19490	20440	21150	22080	22790	23490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.