


EARTHMAX SR 30 M



| | |
|---------------------|--|
| TIRE SIZE | 23.5 R 25 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | LOADER / DOZER / ARTICULATED DUMP TRUCK (ADT) |
| VERSION | CUT RESISTANT COMPOUND |
| TL/TT | TL |
| LI/SS | 185 B ; 195 A2 |

DIMENSIONS IS STANDARD

| | | | |
|-----------------|----------|--------------------|-------|
| OD (MM) | 1605 | TRA CODE | E3/L3 |
| SLR (MM) | 711 | STAR RATING | ★★★ |
| RC (MM) | 4797 | | |
| RIM REC | 19.5/2.5 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 | 5.25 |
|------------|-------|-------|-------|-------|-------|------|
| 50 | 7500 | 7750 | 8250 | 8500 | 9000 | 9250 |
| 10 | 10300 | 10600 | 11200 | 11500 | 12150 | - |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.