


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 650/65 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOTORSTARK TRAKTOR / TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	174 D

## DIMENSIONER US STANDARD

<b>USA CODE</b>	94062102	<b>RC (IN)</b>	227.3
<b>SW (IN)</b>	25.6	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	75.3	<b>RIM ALT</b>	DW 21 B
<b>SLR (IN)</b>	33.5	<b>ECE</b>	E11-106R-005713

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	6840	7910	8990	10210	11140	12090	13440
<b>FROM 40 TO 25</b>	7530	8710	9890	11220	12260	13290	14770
20	7670	8870	10070	11440	12500	13560	15060
12	7830	9050	10270	11660	12740	13820	15350
5	8280	9580	10870	12330	13480	14620	16250
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	10540	12190	13830	15710	17150	18610	20680
5 HT	7670	8870	10070	11440	12500	13560	15060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.