


FLOTATION 648

TIRE SIZE	500/60 - 22.5
UM	IS STANDARD
CONSTRUCTION	 BIAS
MACHINERY	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	153 A8/149 B
LI/SS FREE ROLLING	165 A8/161 B



DIMENSIONES IS STANDARD

SW (MM)	500	RIM REC	AG 16.00
OD (MM)	1170	RIM ALT	15.00; 17.00
SLR (MM)	510	ECE	E11-106R-004390
RC (MM)	3489	PR	18

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.40	3.50	3.60
10 FR	6970	7090	7210
20 FR	6275	6380	6940
30 FR	5580	5675	5770
40 FR	4980	5065	5150
50 FR	4480	4560	4625
10 DW	4940	5025	5110
20 DW	4450	4525	4600
30 DW	3955	4020	4090
40 DW	3530	3590	3650
50 DW	3175	3230	3250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.