

# AGRIMAX RT 657

|                  |                                                   |
|------------------|---------------------------------------------------|
| <b>TIRE SIZE</b> | <b>440/65 R 20</b>                                |
| <b>UM</b>        | US STANDARD                                       |
| <b>MACHINERY</b> | TRAUBENERNTEMASCHINE /<br>TRACTOR / ERNTEMASCHINE |
| <b>VERSION</b>   | STANDARD                                          |
| <b>TIRE TYPE</b> | TL                                                |
| <b>LI/SS</b>     | 138 D ; 141 A8                                    |



## ABMESSUNGEN US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA-CODE</b> | 94042753 | <b>RC (IN)</b> | 127.6          |
| <b>SW (IN)</b>  | 17.4     | <b>RIM REC</b> | W 14 L         |
| <b>OD (IN)</b>  | 42.5     | <b>RIM ALT</b> | W 13 ; W 15 L  |
| <b>SLR (IN)</b> | 18.9     | <b>ECE</b>     | E4-106R-000760 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35   |
|-------------|------|------|------|------|------|------|------|------|
| <b>40</b>   | 2450 | 2870 | 3280 | 3650 | 4010 | 4320 | 4790 | 5200 |
| <b>30</b>   | 2580 | 3010 | 3450 | 3840 | 4210 | 4540 | 5040 | 5470 |
| <b>25</b>   | 2680 | 3130 | 3580 | 3980 | 4380 | 4720 | 5220 | 5680 |
| <b>20</b>   | 2820 | 3300 | 3780 | 4200 | 4620 | 4970 | 5510 | 5990 |
| <b>5 LT</b> | 3280 | 3850 | 4400 | 4890 | 5380 | 5800 | 6430 | 6980 |
| <b>5 HT</b> | 2820 | 3300 | 3780 | 4200 | 4620 | 4970 | 5510 | 5990 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.