

# AS 2001

|                     |                  |
|---------------------|------------------|
| <b>TIRE SIZE</b>    | <b>18.4 - 26</b> |
| <b>UM</b>           | US STANDARD      |
| <b>CONSTRUCTION</b> | ⊠ BIAS           |
| <b>MACHINERY</b>    | TRATTORE         |
| <b>VERSIONE</b>     | STANDARD         |
| <b>TIRE TYPE</b>    | TL               |
| <b>LI/SS</b>        | 142 A8           |



## DIMENSIONI US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CODICE USA</b> | 94002801 | <b>RC (IN)</b> | 167.3           |
| <b>SW (IN)</b>    | 18.4     | <b>RIM REC</b> | W 16 L          |
| <b>OD (IN)</b>    | 58.1     | <b>RIM ALT</b> | W 15 L          |
| <b>SLR (IN)</b>   | 25.6     | <b>ECE</b>     | E11-106R-003507 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>32</b> |
| 25               | 5840      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.