


AGRIMAX SPARGO

TIRE SIZE	VF 420/95 R 50
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTEUR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	177 D



DIMENSIONS US STANDARD

CODE USA	94051380	RC (IN)	244.5
SW (IN)	16.5	RIM REC	DW 14
OD (IN)	81.4	RIM ALT	DW 13; W 13; W 14
SLR (IN)	37.1	ECE	E4-106R-002651

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	20	23	26	29	32	35	38	41	44	47	49	52
45	8190	9080	9960	10390	10980	11270	11570	12150	12740	13180	13760	14200	14640
FROM 40 TO 25	9010	9980	10940	11420	12070	12390	12710	13350	14000	14490	15130	15610	16100
20	9190	10180	11160	11660	12310	12640	12970	13620	14280	14780	15430	15920	16420
12	9370	10380	11380	11880	12550	12880	13220	13880	14550	15060	15720	16230	16740
5	9910	10970	12040	12570	13280	13630	13980	14690	15400	15930	16640	17170	17710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.