

# RIB 713

<b>TIRE SIZE</b>	IF 320/70 R 15
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STUBBLE RESISTANT
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	146 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94050710	<b>RC (IN)</b>	102.0
<b>SW (IN)</b>	12.6	<b>RIM REC</b>	W10
<b>OD (IN)</b>	32.4	<b>ECE</b>	E11-106R-003959
<b>SLR (IN)</b>	14.4	<b>TRA CODE</b>	I1

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	73	75
<b>FROM 5 TO 40 MPH</b>	1880	2400	2920	3310	3820	4340	4790	5250	5760	6470	6610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.