


AGRIMAX SPARGO SB

TIRE SIZE	VF 380/95 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATTORE / IRRORAZIONE
VERSIONE	STEEL BELTED
TIRE TYPE	TL
LI/SS	165 D



DIMENSIONI IS STANDARD

SW (MM)	395	RIM REC	W 13
OD (MM)	1690	RIM ALT	W 12
SLR (MM)	767	ECE	E11-106R-0010942
RC (MM)	5116	SRI	800

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2
70	2530	2810	3145	3435	3625	3765	3905	4050	4240	4435	4575	4765
FROM 65 TO 40	2730	3035	3400	3710	3915	4065	4225	4380	4585	4790	4945	5150
30	2790	3100	3470	3785	3995	4150	4310	4470	4680	4890	5045	5255
20	2845	3160	3535	3860	4075	4235	4395	4555	4770	4985	5150	5360
10	3005	3340	3740	4080	4310	4475	4645	4815	5045	5270	5440	5665

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.