


# AGRIMAXFACTOR

<b>TIRE SIZE</b>	<b>360/70 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	129 D ; 132 A8



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	357	<b>RIM REC</b>	W 11
<b>OD (MM)</b>	1042	<b>RIM ALT</b>	W 10 ; W 12
<b>SLR (MM)</b>	470	<b>ECE</b>	E11-106R-0011928
<b>RC (MM)</b>	3107	<b>SRI</b>	550

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2	2.4
65	760	890	1020	1150	1280	1390	1650	1850
50	800	935	1070	1210	1345	1460	1735	1945
40	820	960	1100	1240	1380	1500	1780	2000
30	875	1025	1175	1325	1470	1600	1900	2130
10 LT	1020	1195	1365	1540	1715	1860	2210	2480
10HT	875	1025	1175	1325	1470	1600	1900	2130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.