

# PL 801

<b>TIRE SIZE</b>	<b>7.00 - 12</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	RASTRILLO HILERADOR ROTATIVO / COSECHADORA / CARRETILLA ELEVADORA / COSECHADORA / MAQUINARIA AGRÍCOLA / CARRETILLA ELEVADORA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TT



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94007219	<b>ECE</b>	E11-106R-003398
<b>SW (IN)</b>	7.4	<b>PR</b>	14
<b>OD (IN)</b>	27.2		
<b>RIM REC</b>	5.00 S		

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>131</b>
<b>15 LOAD WHEEL</b>	6075
<b>15 STEER WHEEL</b>	4675
<b>5 OTHER VEHICLES</b>	6075
<b>15 OTHER VEHICLES</b>	4675
<b>STATIC SIDE LOADER</b>	7055

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.