


# AGRIMAX SPARGO SB

<b>TIRE SIZE</b>	<b>VF 380/90 R 50</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTOR / BESPRUTNINGSBIL
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	175 D



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	400	<b>RIM REC</b>	W13
<b>OD (MM)</b>	1954	<b>RIM ALT</b>	W12;DW13
<b>SLR (MM)</b>	903	<b>ECE</b>	E11-106R-0010177
<b>RC (MM)</b>	5986	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
<b>70</b>	2705	3015	3395	3710	3895	4085	4210	4335	4555	4775	4965	5150	5310	5465	5625	5780	6030	6280
<b>FROM 65 TO 40</b>	2970	3315	3730	4075	4280	4485	4625	4765	5005	5245	5455	5660	5835	6005	6180	6350	6625	6900
<b>30</b>	3030	3380	3805	4155	4365	4580	4720	4860	5105	5355	5565	5775	5950	6125	6305	6480	6760	7040
<b>20</b>	3090	3450	3880	4240	4455	4670	4815	4955	5210	5460	5675	5890	6070	6250	6430	6610	6895	7180
<b>10</b>	3265	3645	4100	4480	4710	4935	5090	5240	5505	5770	6000	6225	6415	6605	6795	6985	7290	7590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.