

FLOTATION 648

| | |
|---------------------------|--|
| TIRE SIZE | 500/55 - 20 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | ПРЕСС-ПОДБОРЩИК / КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 138 A8/134 B |
| LI/SS FREE ROLLING | 150 A8/146 B |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94039234 | RC (IN) | 124.1 |
| SW (IN) | 20.0 | RIM REC | 16.00 |
| OD (IN) | 41.7 | ECE | E11-106R-003369 |
| SLR (IN) | 18.0 | PR | 12 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 29 | 32 | 35 |
|-----------|------|------|-------|
| 5 FR | 9290 | 9830 | 10340 |
| 10 FR | 8370 | 8850 | 9300 |
| 20 FR | 7430 | 7860 | 8270 |
| 25 FR | 6640 | 7020 | 7390 |
| 30 FR | 5970 | 6320 | 6610 |
| 5 DW | 6550 | 6930 | 7290 |
| 10 DW | 5890 | 6240 | 6560 |
| 20 DW | 5240 | 5540 | 5830 |
| 25 DW | 4670 | 4950 | 5200 |
| 30 DW | 4210 | 4450 | 4670 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.