

FLOTATION 648

TIRE SIZE	700/40 - 22.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	HD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	160 A8/156 B
LI/SS FREE ROLLING	173 A8/169 B



ABMESSUNGEN US STANDARD

USA-CODE	94027903	RC (IN)	139.3
SW (IN)	27.6	RIM REC	AG 24.00
OD (IN)	46.1	ECE	E4-106R-002281
SLR (IN)	20.1	PR	18

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	41	44	46
5 FR	18550	19230	20060
10 FR	16700	17390	18050
20 FR	14840	15450	16050
25 FR	13250	13800	14330
30 FR	11930	12420	12790
5 DW	12840	13380	13890
10 DW	11550	12040	12500
20 DW	10270	10700	11110
25 DW	9170	9560	9920
30 DW	8260	8600	8820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.