

AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 460/85 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZADOR AGRÍCOLA / VINDIMADORA / TRATOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 149 A8/B |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 475 | RIM REC | W 16 L |
| OD (MM) | 1747 | RIM ALT | W 14 L ; W 15 L |
| SLR (MM) | 785 | ECE | E4-106R-000618 |
| RC (MM) | 5205 | SRI | 825 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 50 | 1790 | 2080 | 2375 | 2665 | 2960 | 3250 |
| 40 | 1790 | 2080 | 2375 | 2665 | 2960 | 3250 |
| 30 | 1915 | 2230 | 2545 | 2855 | 3170 | 3480 |
| 10 LT | 2400 | 2790 | 3180 | 3575 | 3965 | 4355 |
| 10 HT | 1915 | 2230 | 2545 | 2855 | 3170 | 3480 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.