


# MULTIMAX MP 522

<b>TIRE SIZE</b>	<b>480/80 R 26 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	KOMPAKTHJULLASTARE / TELESKOPLASTARE / KOMPAKTHJULLASTARE / TELESKOPLASTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	167 A8/B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94073108	<b>RC (IN)</b>	168.8
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	DW 15 L
<b>OD (IN)</b>	56.2	<b>RIM ALT</b>	DW 16 L
<b>SLR (IN)</b>	25.1	<b>ECE</b>	E11-106R-008146

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
<b>30</b>	5680	6210	6730	7260	7800	8330	8860	9390	9920	10450	10970	11500	12010	-	-
<b>25</b>	5680	6210	6730	7260	7800	8330	8860	9390	9920	10450	10970	11500	12010	-	-
<b>20</b>	6150	6710	7270	7830	8390	8950	9510	10060	10630	11190	11750	12300	12860	-	-
<b>15</b>	6370	6960	7540	8110	8700	9280	9870	10440	11020	11610	12180	12760	13340	-	-
<b>5 CYC.</b>	7050	7840	8620	9400	10180	10970	11750	12530	13320	14100	14880	16450	18020	-	-
<b>STATIC</b>	10800	12000	13200	14410	15610	16810	18010	19210	20410	21620	22820	24020	25230	26430	27630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.