


AGRIMAX RT 600

| | |
|--------------|--|
| TIRE SIZE | 650/75 R 32 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | COSECHADORA / ESPARCIDOR / TRACTOR / MAQUINARIA AGRÍCOLA |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 172 A8/B |



DIMENSIONES IS STANDARD

| | | | |
|----------|------|---------|-------------------|
| SW (MM) | 655 | RIM REC | DW 21 B |
| OD (MM) | 1789 | RIM ALT | DW 20 B ; DW 23 B |
| SLR (MM) | 807 | ECE | E11-106R-004755 |
| RC (MM) | 5416 | SRI | 850 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.0 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.4 | 3.8 |
|------------|------|------|------|------|------|------|------|-------|-------|-------|
| 50 | 2900 | 3340 | 4095 | 4475 | 4915 | 5355 | 5800 | 6300 | - | - |
| 40 | 2900 | 3340 | 4095 | 4475 | 4915 | 5355 | 5800 | 6300 | - | - |
| 30 | 3105 | 3575 | 4385 | 4790 | 5265 | 5735 | 6210 | 6745 | - | - |
| 10 LT | 3885 | 4480 | 5490 | 6000 | 6590 | 7180 | 7770 | 8445 | - | - |
| 10 HT | 3105 | 3575 | 4385 | 4790 | 5265 | 5735 | 6210 | 6745 | - | - |
| 10 CYC. | - | 4770 | 6105 | 6695 | 7765 | 8515 | 9320 | 10125 | 10285 | 10710 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.