

FL 630 SUPER

TIRE SIZE	580/65 R 22.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MAȘINĂ DE ÎMPRĂȘTIAT / CISTERNĂ / REMORCĂ / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	166 D



DIMENSIUNI IS STANDARD

SW (MM)	577	RIM REC	AG 18.00
OD (MM)	1326	RIM ALT	AG 16.00; AG 17.00; AG 20.00
SLR (MM)	594	ECE	E4-106R-001416
RC (MM)	4058	SRI	625

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1560	1805	2050	2440	2880	3295	3660	4095	4485	4875
65	1700	1965	2230	2650	3130	3580	3975	4455	4880	5300
50	2055	2375	2695	3210	3785	4335	4815	5390	5905	6415
40	2310	2670	3030	3605	4255	4870	5410	6060	6635	7210
25	2680	3100	3520	4190	4945	5655	6285	7035	7705	8375
10	3055	3535	4010	4770	5630	6440	7155	8015	8780	9540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.