


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 750/70 R 44</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE A ELEVATA POTENZA / TRATTORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	186 D



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94066926	<b>RC (IN)</b>	253.9
<b>SW (IN)</b>	29.9	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	85.6	<b>RIM ALT</b>	DW 24 B
<b>SLR (IN)</b>	37.7	<b>ECE</b>	E11-106R-006765

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	9530	11060	12590	14300	15830	17350	19060
<b>FROM 40 TO 25</b>	10470	12150	13820	15710	17380	19060	20940
20	10680	12400	14110	16030	17740	19440	21360
12	10890	12640	14380	16340	18090	19830	21780
5	11520	13370	15210	17280	19120	20960	23040
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	14660	17010	19360	21990	24340	26690	29320
5 HT	10680	12400	14110	16030	17740	19440	21360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.