

# PL 801

<b>TIRE SIZE</b>	7.00 - 12
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	RANGHINATORE / MIETITREBBIA / CARRELLO ELEVATORE / MIETITREBBIA / ATTREZZI AGRICOLI / CARRELLO ELEVATORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TT



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94007196	<b>ECE</b>	E11-106R-003567
<b>SW (IN)</b>	7.4	<b>PR</b>	12
<b>OD (IN)</b>	27.2		
<b>RIM REC</b>	5.00 S		

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>123</b>
<b>15 LOAD WHEEL</b>	5910
<b>15 STEER WHEEL</b>	4540
<b>5 OTHER VEHICLES</b>	5910
<b>15 OTHER VEHICLES</b>	4540
<b>STATIC SIDE LOADER</b>	6855

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.