


# RIDEMAX FL 690

|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>30.5L R 32</b>                                                                        |
| <b>UM</b>           | US STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TANKER / TRAILER / IMPLEMENTS / TRAILER                                                  |
| <b>VERSION</b>      | STANDARD                                                                                 |
| <b>TIRE TYPE</b>    | TL                                                                                       |
| <b>LI/SS</b>        | 184 A8 ; 181 B                                                                           |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94033836 | <b>RC (IN)</b> | 213.8           |
| <b>SW (IN)</b>  | 31.1     | <b>RIM REC</b> | DH 27 B         |
| <b>OD (IN)</b>  | 70.9     | <b>RIM ALT</b> | DW 27 B         |
| <b>SLR (IN)</b> | 31.7     | <b>ECE</b>     | E11-106R-002986 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12    | 15    | 20    | 23    | 29    | 35    | 41    | 44    |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 8370  | 9640  | 11640 | 12550 | 14370 | 16000 | 17460 | 18190 |
| 25        | 9630  | 11090 | 13390 | 14440 | 16530 | 18420 | 20090 | 20920 |
| 20        | 10880 | 12530 | 15130 | 16320 | 18680 | 20810 | 22710 | 23640 |
| 15        | 11470 | 13220 | 15960 | 17210 | 19700 | 21930 | 23930 | 24920 |
| 5         | 13320 | 15330 | 18520 | 19960 | 22850 | 25460 | 27780 | 28920 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.