


AGRIMAX SPARGO

TIRE SIZE	VF 320/90 R 46
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTEUR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	165 D



DIMENSIONS US STANDARD

CODE USA	94513772	RC (IN)	209.3
SW (IN)	12.7	RIM REC	W 11
OD (IN)	68.6	RIM ALT	W 10; DW 10; W 10 L; DW 11
SLR (IN)	31.9	ECE	E11-106R-0010077

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	20	23	26	29	32	35	38	41	44	47	49	52	55	58	61	64
45	4520	5050	5680	6210	6520	6840	7050	7260	7620	8000	8300	8620	8890	9150	9410	9670	10090	10510
FROM 40 TO 25	4890	5460	6140	6710	7050	7390	7620	7840	8240	8640	8980	9320	9610	9890	10170	10450	10910	11360
20	4990	5570	6270	6850	7190	7540	7780	9010	8400	8810	9160	9510	9800	10090	10380	10660	11130	11590
12	5090	5680	6390	6980	7330	7690	7930	8160	8580	8990	9340	9700	9990	10290	10590	10880	11360	11820
5	5380	6000	6750	7380	7750	8130	8380	8620	9070	9510	9880	10260	10560	10870	11190	11500	12000	12490
UPTO 10 CYC.	6630	7400	8320	9090	9550	10010	10320	10630	11170	11700	12160	12630	13010	13400	13780	14170	14790	15390
UPTO 20 CYC.	5560	6200	6970	7620	8010	8390	8650	8910	9360	9820	10200	10590	10910	11230	11560	11880	12390	12900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.