


# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>360/70 R 20</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IRRORAZIONE / TRATTORE / VENDEMMIATRICE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	129 A8/B



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94021949	<b>RC (IN)</b>	122.9
<b>SW (IN)</b>	14.1	<b>RIM REC</b>	W 11
<b>OD (IN)</b>	41.0	<b>RIM ALT</b>	W 10 ; W 12
<b>SLR (IN)</b>	18.5	<b>ECE</b>	E4-106R-000647

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
<b>30</b>	1920	2200	2540	2850	3190	3520	3800	4080
<b>25</b>	1920	2200	2540	2850	3190	3520	3800	4080
<b>20</b>	2060	2360	2710	3060	3410	3760	4070	4360
<b>5 LT</b>	2580	2950	3390	3840	4270	4710	5090	5470
<b>5 HT</b>	2060	2360	2710	3060	3410	3760	4070	4360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.