

# AW 708

<b>TIRE SIZE</b>	<b>400/60 - 15.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	149 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	405	<b>RIM REC</b>	AG 13.00
<b>OD (MM)</b>	875	<b>ECE</b>	E4-106R-001543
<b>SLR (MM)</b>	380	<b>PR</b>	18
<b>RC (MM)</b>	2564		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.50
10 FR	4550
25 FR	3870
30 FR	3640
40 FR	3250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.