

# TF 8181

|                     |                                 |
|---------------------|---------------------------------|
| <b>TIRE SIZE</b>    | <b>6.00 - 16</b>                |
| <b>UM</b>           | IS STANDARD                     |
| <b>CONSTRUCTION</b> |                                 |
| <b>MACHINERY</b>    | 2WD TRACTOR / TRACTOR / TRAILER |
| <b>VERSION</b>      | SPECIAL                         |
| <b>TIRE TYPE</b>    | TT                              |
| <b>LI/SS</b>        | 88 A6                           |



## DIMENSIONS IS STANDARD

|                 |      |                |                     |
|-----------------|------|----------------|---------------------|
| <b>SW (MM)</b>  | 173  | <b>RIM REC</b> | 4.50 E              |
| <b>OD (MM)</b>  | 745  | <b>RIM ALT</b> | 4.00 E; 5 K; 5.00 F |
| <b>SLR (MM)</b> | 350  | <b>ECE</b>     | E11-106R-004410     |
| <b>RC (MM)</b>  | 2220 | <b>PR</b>      | 6                   |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.30</b> |
| 30                | 560         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.