


RIDEMAX IT 697 (M+S)



| | |
|---------------------|--|
| TIRE SIZE | 650/85 R 38 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 178 D ; 183 A8 |

DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-------------------|
| SW (MM) | 709 | RIM REC | DW 23 B |
| OD (MM) | 2071 | RIM ALT | DW 20 B ; DW 21 B |
| SLR (MM) | 974 | ECE | E11-106R-006761 |
| RC (MM) | 6280 | SRI | 975 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|
| 65 | 3525 | 4350 | 5100 | 5925 | 6675 | 7500 |
| 50 | 3805 | 4700 | 5510 | 6400 | 7210 | 8100 |
| 40 | 4115 | 5075 | 5950 | 6915 | 7790 | 8750 |
| 30 | 4230 | 5220 | 6120 | 7110 | 8010 | 9000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.