


AGRIMAX RT 855

TIRE SIZE	320/85 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
VERSION	SPECIAL
TL/TT	TL
LI/SS	143 A8/B



DIMENSIONS US STANDARD

USA CODE	94047543	RC (IN)	180.3
SW (IN)	13.0	RIM REC	W 11
OD (IN)	59.4	RIM ALT	W 9 ; W 10 ; DW 10
SLR (IN)	27.6	ECE	E4-106R-000781

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	17	23	29	35	41	46	52
30	2170	2520	3310	4030	4390	4700	5110	5530	6000
25	2170	2520	3310	4030	4390	4700	5110	5530	6000
20	2330	2710	3550	4320	4710	5030	5480	5930	6440
5 LT	2910	3390	4440	5400	5890	6290	6860	7420	8060
5 HT	2330	2710	3550	4320	4710	5030	5480	5930	6440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.