


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 480/80 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	166 D



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	1733	<b>RIM ALT</b>	DW 15 L
<b>SLR (MM)</b>	774	<b>ECE</b>	E11-106R-007168
<b>RC (MM)</b>	5169	<b>SRI</b>	825

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2270	2605	2990	3375	3760	4150	4535	4820
FROM 65 TO 40	2495	2865	3290	3710	4135	4560	4985	5300
30	2545	2920	3355	3785	4220	4650	5085	5405
20	2590	2980	3420	3860	4300	4740	5180	5510
10	2745	3150	3615	4085	4550	5015	5485	5830
*UPTO 10 CYC WITH FRONT LOADER	3490	4010	4605	5195	5790	6385	6975	7420
10 HT	2545	2830	3355	3785	4220	4650	5085	5405

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.