


# AGRIMAXFACTOR

<b>TIRE SIZE</b>	<b>580/70 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATOR
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155 D ; 158 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94071050	<b>RC (IN)</b>	214.8
<b>SW (IN)</b>	22.7	<b>RIM REC</b>	W 18 L
<b>OD (IN)</b>	71.9	<b>RIM ALT</b>	DW18L;DD18L
<b>SLR (IN)</b>	32.4	<b>ECE</b>	E11-106R-007608

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	4710	5470	6240	7010	7780	8540
30	4940	5740	6560	7360	8170	8970
25	5150	6000	6830	7680	8520	9360
20	5410	6290	7190	8070	8950	9830
5 LT	6300	7330	8370	9390	10430	11450
5 HT	5410	6290	7190	8070	8950	9830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.