


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 650/60 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	174 D

## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94074808	<b>RC (IN)</b>	219.1
<b>SW (IN)</b>	26.0	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	72.6	<b>RIM ALT</b>	DW21B
<b>SLR (IN)</b>	32.8	<b>ECE</b>	E11-106R-008774

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	6170	7120	8190	9130	10210	11140	12490	13440
<b>FROM 40 TO 25</b>	6790	7830	9010	10040	11220	12260	13730	14770
20	6920	7970	9180	10230	11440	12490	14000	15060
12	7050	8130	9360	10440	11660	12740	14270	15350
5	7470	8610	9910	11040	12350	13480	15100	16250
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	9500	10960	12610	14050	15710	17160	19220	20680
5 HT	6920	7970	9180	10230	11440	12490	14000	15060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.