

# EARTHMAX SR 42



**EARTHMAX**  
RADIAL OTR TIRES

# EARTHMAX SR 42

EARTHMAX SR 42 is a radial OTR tyre specially engineered for haul trains in mining and logging applications. The distinctive tread design provides outstanding traction and lateral stability as well as good braking and cornering performance on rough and gravel terrains even on ice and snow. Indeed, the special cut-and-wear-resistant tread compound is particularly suitable in extreme cold climate. EARTHMAX SR 42 features an All Steel casing for excellent durability and a long service life.



|      | SIZE       | TT/TL | TRA CODE | STAR RATING | LI/SS | RIM                                                                               |                                                                                   | TKPH | O.W.<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | THREAD DEPTH | VERSION |
|------|------------|-------|----------|-------------|-------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------|--------------|------------|-------------|------------|--------------|---------|
|      |            |       |          |             |       | REC RIM                                                                           | ALT RIM                                                                           |      |              |            |             |            |              |         |
|      |            |       |          |             |       |  |  |      |              |            |             |            |              |         |
| Ø24" | 14.00 R 24 | TL    | E4       | ***         | 171 B | 10.00W                                                                            | --                                                                                | 105  | 380          | 1412       | 652         | 4231       | 38           | CR      |
| Ø25" | 14.00 R 25 | TL    | E4       | ***         | 171 B | 10.00/2.0                                                                         | --                                                                                | 105  | 380          | 1412       | 652         | 4231       | 38           | CR      |
|      | 14.00 R 25 | TL    | E4       | ***         | 171 B | 10.00/1.5                                                                         | --                                                                                | 105  | 380          | 1412       | 652         | 4231       | 38           | CR      |

CR: CUT RESISTANT COMPOUND

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
|  |  |  |  |
| B                                                                                   | 171 kg                                                                              |                                                                                     |                                                                                     |

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index