


AGRIMAX SPARGO

| | |
|---------------------|--|
| TIRE SIZE | VF 380/105 R 50 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTEUR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 179 D |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------------------|
| CODE USA | 94048113 | RC (IN) | 244.5 |
| SW (IN) | 15.7 | RIM REC | W 13 A |
| OD (IN) | 80.7 | RIM ALT | W 12; DW 12; DW 13; DW 13 L |
| SLR (IN) | 36.8 | ECE | E4-106R-002397 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17 | 20 | 23 | 26 | 29 | 32 | 35 | 38 | 41 | 44 | 47 | 49 | 52 | 55 | 58 | 61 | 64 |
|---------------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 7460 | 8390 | 9160 | 9640 | 10100 | 10410 | 10720 | 11350 | 11810 | 12270 | 12750 | 13210 | 13520 | 13990 | 14300 | 14920 | 15550 |
| FROM 40 TO 25 | 8210 | 9230 | 10080 | 10600 | 11100 | 11450 | 11790 | 12470 | 12990 | 13500 | 14010 | 14520 | 14860 | 15380 | 15720 | 16410 | 17090 |
| 20 | 8360 | 9410 | 10280 | 10810 | 11330 | 11680 | 12020 | 12720 | 13240 | 13760 | 14290 | 14810 | 15160 | 15680 | 16030 | 16730 | 17430 |
| 12 | 8530 | 9590 | 10490 | 11020 | 11550 | 11910 | 12260 | 12970 | 13510 | 14040 | 14570 | 15110 | 15460 | 15990 | 16350 | 17060 | 17770 |
| 5 | 9020 | 10150 | 11080 | 11660 | 12220 | 12590 | 12970 | 13720 | 14280 | 14840 | 15410 | 15980 | 16350 | 16910 | 17290 | 18040 | 18800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.