

# COMMANDER (F)

|                     |                       |
|---------------------|-----------------------|
| <b>TIRE SIZE</b>    | 6.50 - 16             |
| <b>UM</b>           | US STANDARD           |
| <b>CONSTRUCTION</b> | BIAS                  |
| <b>MACHINERY</b>    | TRACTOR 2WD / TRACTOR |
| <b>VERSION</b>      | STANDARD              |
| <b>TIRE TYPE</b>    | TT                    |
| <b>LI/SS</b>        | 95 A8                 |



## DIMENSIUNI US STANDARD

|                 |          |                |                        |
|-----------------|----------|----------------|------------------------|
| <b>USA CODE</b> | 94051809 | <b>RC (IN)</b> | 91.8                   |
| <b>SW (IN)</b>  | 7.2      | <b>RIM REC</b> | 4.50 E                 |
| <b>OD (IN)</b>  | 30.3     | <b>RIM ALT</b> | 4.00 E; 5.00 F; 5.50 F |
| <b>SLR (IN)</b> | 14.3     | <b>ECE</b>     | E11-106R-004109        |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>72</b> |
| 25               | 690       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.