



IS standard



GROWING TOGETHER

# MINE TRAX



PRODUCT DATA SHEET



Bias



R-4



A8



154

**Technologies**



Extra Deep Tread



Reinforced Carcass

**Performance**



Cut and Chip Resistance



Durability



Traction



Stability



High Load Capacity



High Puncture Resistance



# MINE TRAX

MINE TRAX is a bias-ply tyre designed for demanding requirements in underground mining operations. Specifically intended for mine utility vehicles, the tyre performs reliably in harsh underground conditions across a variety of operations and maintenance tasks, including material handling and cable installation. MINE TRAX features an extra-deep tread and a specially formulated compound that provide outstanding resistance to punctures and wear, even on abrasive and uneven surfaces. The non-directional tread pattern provides multi-directional versatility, while wide tread blocks ensure excellent traction and enhance vehicle stability. The large contact area and high ply rating deliver superior load capacity and maintain stability during lifting and aerial maneuvers, ensuring operator safety. In addition, the reinforced carcass and the cut-resistant sidewall protect against lateral damage, reducing machine downtime and extending the tyre's service life.

Tyre size	Type	TRA CODE	PR	LI/SS	Version	TKPH	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM		
												Rec.	Alt.	
Ø 24"	19.5 L - 24	TL	R-4	14	154 A8	STD	-	500	1330	-	-	45	DW 16 L	-

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference