


AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 340/85 R 36 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 132 A8/B |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94033089 | RC (IN) | 177.4 |
| SW (IN) | 13.9 | RIM REC | W 12 |
| OD (IN) | 58.7 | RIM ALT | W 11 |
| SLR (IN) | 27.1 | ECE | E4-106R-000763 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-------------|------|------|------|------|------|------|
| 30 | 2420 | 2820 | 3220 | 3620 | 4010 | 4410 |
| 25 | 2420 | 2820 | 3220 | 3620 | 4010 | 4410 |
| 20 | 2600 | 3020 | 3450 | 3870 | 4300 | 4720 |
| 5 LT | 3250 | 3790 | 4320 | 4850 | 5380 | 5910 |
| 5 HT | 2600 | 3020 | 3450 | 3870 | 4300 | 4720 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.