


# RM 500

|              |  |
|--------------|--|
| TIRE SIZE    | 600/65 R 28  |
| UM           | IS STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | КОМБАЙН  |
| VERSION      | STEEL BELTED   |
| TIRE TYPE    | TL   |
| LI/SS        | 177 A8 ; 165 A8  |



## РАЗМЕРЫ IS STANDARD

|          |      |         |                 |
|----------|------|---------|-----------------|
| SW (MM)  | 590  | RIM REC | W 18 L          |
| OD (MM)  | 1486 | RIM ALT | W 20 L          |
| SLR (MM) | 640  | ECE     | E11-106R-007699 |
| RC (MM)  | 4340 | SRI     | 700             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR      | 0.8  | 1.0  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  |
|-----------------|------|------|------|------|------|------|------|
| 40 FREE ROLLING | 3070 | 3505 | 3945 | 4820 | 5550 | 6425 | 7300 |
| 40 DRIVE WHEEL  | 2165 | 2475 | 2785 | 3400 | 3915 | 4535 | 5150 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.