

# MP 567

<b>TIRE SIZE</b>	<b>11.5/80 - 15.3</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO / VEHÍCULO UNIVERSAL
<b>VERSIÓN</b>	IMPLEMENT
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	130 A8
<b>LI/SS FREE ROLLING</b>	143 A8



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94057603	<b>RC (IN)</b>	101.5
<b>SW (IN)</b>	11.5	<b>RIM REC</b>	9.0
<b>OD (IN)</b>	34.2	<b>ECE</b>	E11-106R-003392
<b>SLR (IN)</b>	15.5	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>87</b>
25 FR	6010
25 DW	4190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.