

AS 504

TIRE SIZE	7.50 - 16
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	HD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	99 A8
LI/SS FREE ROLLING	112 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	209	RIM REC	5.50 F
OD (MM)	803	RIM ALT	4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F
SLR (MM)	372	ECE	E11-106R-004337
RC (MM)	2475	PR	8

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.20
10 FR	1570
25 FR	1335
30 FR	1255
40 FR	1120
10 DW	1085
25 DW	920
30 DW	870
40 DW	775

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.