

# FS 216

|                     |                        |
|---------------------|------------------------|
| <b>TIRE SIZE</b>    | 24.5 - 32              |
| <b>UM</b>           | IS STANDARD            |
| <b>CONSTRUCTION</b> |                        |
| <b>MACHINERY</b>    | LOG SKIDDER / FORESTRY |
| <b>VERSION</b>      | STEEL BELTED           |
| <b>TIRE TYPE</b>    | TL                     |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 622  | <b>RIM REC</b> | DH 21           |
| <b>OD (MM)</b>  | 1831 | <b>RIM ALT</b> | DH 21 B         |
| <b>SLR (MM)</b> | 805  | <b>ECE</b>     | E11-106R-003421 |
| <b>RC (MM)</b>  | 5380 | <b>PR</b>      | 16              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.40 | 2.10 |
|------------|------|------|
| 10         | 7000 | -    |
| 30         | -    | 5000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.