DATA SHEET

PRINTED ON
23-04-2026

AS 504

TIRE SIZE	**11.0/65 - 12**
UM	US STANDARD
CONSTRUCTION	
MACHINERY	TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	101 A8
LI/SS FREE ROLLING	114 A8

DIMENSIONS US STANDARD

USA CODE	94019434	**RC (IN)**	81.6
SW (IN)	10.7	**RIM REC**	9.00
OD (IN)	27.6	**ECE**	E4-106R-002834
SLR (IN)	12.6	**PR**	8

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	42
5 FR	3640
15 FR	3100
20 FR	2910
25 FR	2600
5 DW	2550
15 DW	2160
20 DW	2040
25 DW	1820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..