

# AW 702

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>10.0/75 - 15.3</b>   |
| <b>UM</b>                 | IS STANDARD   |
| <b>CONSTRUCTION</b>       | ❖ BIAS  |
| <b>MACHINERY</b>          | BALPRESS / ARBETSFORDON /<br>SLÄPVAGN / SKÖRDEMASKIN /<br>ARBETSFORDON / SLÄPVAGN |
| <b>VERSION</b>            | STANDARD  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS FREE ROLLING</b> | 135 A8  |



## DIMENSIONER IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 274  | <b>RIM REC</b> | 9.00           |
| <b>OD (MM)</b>  | 760  | <b>ECE</b>     | E4-106R-001880 |
| <b>SLR (MM)</b> | 351  | <b>PR</b>      | 18             |
| <b>RC (MM)</b>  | 2213 |                |                |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>7.10</b> |
|-------------------|-------------|
| 10 FR             | 3050        |
| 25 FR             | 2595        |
| 30 FR             | 2440        |
| 40 FR             | 2180        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.