

# RIB 774 (C)

<b>TIRE SIZE</b>	<b>19.0/45 - 17</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ENFARDADEIRA DE FENO / CEIFEIRA / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	138 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94027330	<b>RC (IN)</b>	99.1
<b>SW (IN)</b>	17.9	<b>RIM REC</b>	16.00
<b>OD (IN)</b>	33.3	<b>ECE</b>	E11-106R-004589
<b>SLR (IN)</b>	15.2	<b>PR</b>	10

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>33</b>
<b>5 FR</b>	7290
<b>15 FR</b>	6190
<b>20 FR</b>	5830
<b>25 FR</b>	5200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.