

# TR 135

|                     |                   |
|---------------------|-------------------|
| <b>TYRE SIZE</b>    | 12.4 - 36         |
| <b>UM</b>           | US STANDARD       |
| <b>CONSTRUCTION</b> | ⊠ BIAS            |
| <b>MACHINERY</b>    | TRACTOR / TRAILER |
| <b>VERSION</b>      | HD                |
| <b>TYRE TYPE</b>    | TL                |
| <b>LI/SS</b>        | 135 A8            |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94053100 | <b>RC (IN)</b> | 179.0           |
| <b>SW (IN)</b>  | 12.8     | <b>RIM REC</b> | W 11            |
| <b>OD (IN)</b>  | 57.7     | <b>RIM ALT</b> | W 9; W 10       |
| <b>SLR (IN)</b> | 27.4     | <b>ECE</b>     | E11-106R-004449 |

## LOAD CAPACITY (LBS/TYRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>60</b> |
| 25               | 4810      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.