

# TR 126

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>6 - 14</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | МИНИ-ТРАКТОР / ТРАКТОР-ТЯГАЧ   |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 63 A8  |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94053513 | <b>RC (IN)</b> | 77.9            |
| <b>SW (IN)</b>  | 6.2      | <b>RIM REC</b> | 5 JA; 5 KB      |
| <b>OD (IN)</b>  | 25.8     | <b>ECE</b>     | E11-106R-003476 |
| <b>SLR (IN)</b> | 12.0     | <b>PR</b>      | 4               |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>28</b> |
| 25               | 600       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.