


AGRIMAX RT 657

TIRE SIZE	600/65 R 28
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	154 D ; 157 A8



DIMENSIONER IS STANDARD

SW (MM)	611	RIM REC	DW 20 B
OD (MM)	1491	RIM ALT	W 18 L
SLR (MM)	670	ECE	E4-106R-000621
RC (MM)	4470	SRI	700

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1800	2100	2365	2625	2890	3115	3450	3750
50	1895	2210	2485	2760	3035	3275	3625	3940
40	1980	2310	2600	2890	3180	3425	3795	4125
30	2075	2420	2720	3025	3325	3585	3970	4315
10 LT	2415	2815	3170	3520	3870	4175	4625	5025
10 HT	2075	2420	2720	3025	3325	3585	3970	4315

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.