


AGRIMAX RT 600

TIRE SIZE	IF 680/85 R 32
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MAȘINĂ DE RECOLTARE / MAȘINĂ DE ÎMPRĂȘTIAT / TRACTOR / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	179 D



DIMENSIUNI IS STANDARD

SW (MM)	682	RIM REC	DW23 B
OD (MM)	1960	RIM ALT	DW21 B
SLR (MM)	846	ECE	E11-106R-006401
RC (MM)	5860	SRI	925

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
FROM 65 TO 40	3640	4185	4805	5425	6045	6665	7285	7750
30	3785	4350	4995	5640	6285	6930	7575	8060
20	3930	4515	5185	5855	6525	7195	7865	8370
10	4620	5310	6100	6885	7675	8460	9250	9840
UPTO 30 CYC	4730	5440	6245	7050	7855	8660	9470	10075
UPTO 15 CYC	5640	6485	7445	8405	9365	10330	11290	12010
10 HT	3785	4350	4995	5640	6285	6930	7575	8060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.