DATA SHEET

PRINTED ON
22-04-2026

AT 621

TIRE SIZE	**12.5/80 - 18**
UM	IS STANDARD
CONSTRUCTION	
MACHINERY	COMPACT LOADER / BACKHOE LOADER / BACKHOE LOADER / LOADER
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS DRIVE WHEEL	129 A8
LI/SS FREE ROLLING	142 A8

DIMENSIONS IS STANDARD

SW (MM)	308	**RIM REC**	W 9
OD (MM)	987	**RIM ALT**	11.0
SLR (MM)	434	**ECE**	E11-106R-005329
RC (MM)	2916	**PR**	12

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.70
10 FR	3710
25 FR	3155
30 FR	2970
40 FR	2650
10 DW	2590
25 DW	2200
30 DW	2070
40 DW	1850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..