


AGRIMAX FORCE



| | |
|---------------------|--|
| TIRE SIZE | IF 650/85 R 42 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MIETITREBBIA / TRATTORE A ELEVATA POTENZA / TRATTORE |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 180 D |

DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|-----------------|----------------|
| SW (MM) | 650 | RIM REC | DW 23 B |
| OD (MM) | 2173 | ECE | E4-106R-001832 |
| SLR (MM) | 965 | SRI | 1025 |
| RC (MM) | 6400 | TRA CODE | R1W |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|----------------------|------|------|------|------|-------|-------|-------|-------|
| 70 | 3420 | 3930 | 4510 | 5095 | 5675 | 6260 | 6840 | 7280 |
| FROM 65 TO 40 | 3760 | 4320 | 4960 | 5600 | 6240 | 6880 | 7520 | 8000 |
| 30 | 3910 | 4490 | 5155 | 5820 | 6485 | 7155 | 7820 | 8320 |
| 20 | 4060 | 4665 | 5355 | 6045 | 6735 | 7430 | 8120 | 8640 |
| 10 | 4775 | 5485 | 6295 | 7110 | 7920 | 8735 | 9550 | 10160 |
| UPTO 30 CYC | 4885 | 5615 | 6445 | 7280 | 8110 | 8940 | 9775 | 10400 |
| UPTO 15 CYC | 5825 | 6695 | 7685 | 8680 | 9670 | 10660 | 11655 | 12400 |
| UPTO 10 CYC | 6390 | 7340 | 8430 | 9520 | 10605 | 11695 | 12780 | 13600 |
| 10 HT | 3910 | 4490 | 5155 | 5820 | 6485 | 7155 | 7820 | 8320 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.