


# EARTHMAX SR 41

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 26.5 R 25  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | HJULLASTARE / BULLDOZER /<br>HJULLASTARE / BULLDOZER                                     |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 193 B ; 202 A2   |



## DIMENSIONER US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>USA CODE</b> | 94041206 | <b>RIM REC</b>     | 22.00/3.0 |
| <b>OD (IN)</b>  | 68.6     | <b>TRA CODE</b>    | E4/L4     |
| <b>SLR (IN)</b> | 30.5     | <b>STAR RATING</b> | ★★★       |
| <b>RC (IN)</b>  | 202.8    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58    | 62    | 65    | 69    | 73    | 76    |
|-----------|-------|-------|-------|-------|-------|-------|
| 30        | 20900 | 21500 | 22700 | 23400 | 24700 | 25400 |
| 5         | 28300 | 29100 | 30900 | 32000 | 33100 | --    |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.