

# AT 621

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 9.00 - 16  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> | ⊠ BIAS   |
| <b>MACHINERY</b>    | KOMPAKTHJULLASTARE /<br>GRÄVLASTARE / GRÄVLASTARE /<br>HJULLASTARE |
| <b>VERSION</b>      | INDUSTRIAL   |
| <b>TIRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 137 A6   |



## DIMENSIONER IS STANDARD

|                |        |            |                 |
|----------------|--------|------------|-----------------|
| <b>SW (MM)</b> | 260    | <b>ECE</b> | E11-106R-005364 |
| <b>OD (MM)</b> | 925    | <b>PR</b>  | 16              |
| <b>RIM REC</b> | 6.50 H |            |                 |
| <b>RIM ALT</b> | 6.00 G |            |                 |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>7.25</b> |
| 30                | 2300        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.